

## 石川鋼材株式会社 取扱鋼材一覧

- |   |   |
|---|---|
| 1 ... 等辺アングル 一般構造用圧延鋼材 SS JIS G3101(1987)       | 19 ... 異形丸棒 JIS G3112(1987)                     |
| 2 ... 不等辺アングル 一般構造用圧延鋼材 SS JIS G3101(1987)      | 20 ... 角鋼 JIS G3101(1987)                       |
| 不等辺不等厚アングル 一般構造用圧延鋼材 SS JIS G3101(1987)         | 21 ... 鋼板 JIS G3101(1987)                       |
| 3 ... チャンネル 一般構造用圧延鋼材 SS JIS G3101(1987)        | 22 ... C形鋼 一般構造用軽量形鋼 JIS G3350(1987)            |
| 4 ... H形鋼 建築構造用圧延材 JIS G3136(1994)              | 23 ... 軽ミゾ形鋼                                    |
| 7 ... 軽量H形鋼 一般構造用溶接軽量H形鋼 SWH400 JIS G3353(1990) | 24 ... スモール角パイプ STKMR                           |
| 8 ... アイビーム 一般構造用圧延鋼材 SS400 JIS G3101(1987)     | 25 ... スーパースモール角パイプ (アール付き)                     |
| 9 ... CT形鋼                                      | 26 ... 中径角形鋼管 一般構造用角形鋼管 STKR400 JIS G3466(1988) |
| 10 ... デッキプレート JIS S3352(1979)                  | 29 ... コラム STKR                                 |
| 11 ... 合成スラブ用デッキプレート                            | 30 ... 電縫管 機械構造用炭素鋼鋼管 STKM11A JIS G3445(1988)   |
| 12 ... レール                                      | 31 ... ガス管 配管用炭素鋼鋼管 SGP JIS G3452(1988)         |
| 13 ... フラットバー JIS G3101(1987)                   | 32 ... 構造用鋼管 一般構造用炭素鋼鋼管 STK400 JIS G3444(1988)  |
| 16 ... 機械構造用炭素鋼 平鋼(標準S50C)                      | 35 ... 配管用アーク溶接炭素鋼鋼管 STPY400 JIS G3457          |
| 17 ... 機械構造用炭素鋼 平鋼 焼なまし材(標準S55C)                | 36 ... 圧力配管用鋼管 JIS G3454(STPG)                  |
| 18 ... 丸棒 JIS G3101(1987)                       | 37 ... 引抜鋼管 (STKM)                              |
|   | 38 ... 楕円パイプ                                    |

こちらに記載の無い製品については下記までお問い合わせください。

石川鋼材株式会社  
〒334-0063  
埼玉県川口市東本郷1丁目5番33号  
TEL.048(284)7761(代)~6 FAX.048(284)7666

等辺アングル 一般構造用圧延鋼材 SS JIS G3101(1987)

カラー 白

サイズ		1.0	5.5	6.0	7.0	8.0	9.0	11.0	12.0
A×B	厚さ								
20×20	3	0.885	4.87						
25×25	3	1.12	6.16						
30×30	3	1.36	7.48						
	5	2.16	11.9						
40×40	3	1.83	10.1	11.0					
	5	2.95	16.2	17.7					
50×50	4	3.06	16.8	18.4	21.4	24.5	27.5	33.7	36.7
	6	4.43	24.4	26.6	31.0	35.4	39.9	48.7	53.2
	8	5.78	31.8						
60×60	4	3.68	20.2	22.1					44.2
	5	4.55	25.0	27.3					54.6
	6	5.41		32.5					
65×65	6	5.91	32.5	35.5	41.4	47.3	53.2	65.0	70.9
	8	7.66	42.1	46.0	53.6	61.3	68.9	84.3	91.9
75×75	6	6.85	37.7	41.1	48.0	54.8	61.6	75.4	82.2
	9	9.96	54.8	59.8	69.7	79.7	89.6	110	120
	12	13.0	71.5	78.0					
80×80	6	7.32	40.3	43.9					
90×90	7	9.59	52.7	57.5	67.1	76.7	86.3	105	115
	10	13.3	73.2	79.8	93.1	106	120	146	160
	13	17.0	93.5	102	119	136	153	187	204
100×100	7	10.7	58.8	64.2	74.9	85.6	96.3	118	128
	10	14.9	82.0	89.4	104	119	134	164	179
	13	19.1	105	115	134	153	172	210	229
130×130	9	17.9	98.4	107	125	143	161	197	215
	12	23.4	129	140	164	187	211	257	281
	15	28.8	158	173	202	230	259	317	346
150×150	12	27.3	150	164	191	218	246	300	328
	15	33.6	185	202	235	269	302	370	403
	19	41.9	230	251	293	335	377	461	503
200×200	15	45.3	249	272	317	362	408	498	544
	20	59.7	328	358	418	478	537	657	716
	25	73.6	405	442	515	589	662	810	883

不等辺アングル 一般構造用圧延鋼材 SS JIS G3101(1987)

サイズ		1.0	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A × B	厚さ									
50 × 75	6	5.67	31.2	34.0	39.7	45.4	51.0	56.7	62.4	68.0
75 × 90	6	7.56	41.6	45.4	52.9	60.5	68.0	75.6	83.2	90.7
	9	11.0	60.5	66.0	77.0	88.0	99.0	110	121	132
75 × 100	7	9.32	51.3	55.9	65.2	74.6	83.9	93.2	103	112
	10	13.0	71.5	78.0	91.0	104	117	130	143	156
	13	16.5	90.8	99.0	116	132	148	165	182	198
75 × 125	7	10.7	58.8	64.2	74.9	85.6	96.3	107	118	128
	10	14.9	82.0	89.4	104	119	134	149	164	179
	13	19.1	105	115	134	153	172	191	210	229
90 × 125	10	16.1	88.6	96.6	113	129	145	161	177	193
	13	20.6	113	124	144	165	185	206	227	247
90 × 150	9	16.4	90.2	98.4	115	131	148	164	180	197
	12	21.5	118	129	150	172	194	215	236	258
100 × 150	9	17.1	94.0	103	120	137	154	171	188	205
	12	22.4	123	134	157	179	202	224	246	269
	15	27.7	152	166	194	222	249	277	305	332

不等辺不等厚アングル 一般構造用圧延鋼材 SS JIS G3101(1987)

サイズ					質量kg/m	5.5	6.0	7.0	8.0	9.0	11.0	12.0
A × B	t1	t2	r1	r2								
200 × 90	9	14	14	7	23.3	128	140	163	186	210	256	280
250 × 90	10	15	17	8.5	29.4	162	176	206	235	265	323	353
	12	16	17	8.5	33.7	185	202	236	270	303	371	404
300 × 90	11	16	19	9.5	36.3	200	218	254	290	327	399	436
	13	17	19	9.5	41.3	227	248	289	330	372	454	496
350 × 100	12	17	22	11	45.3	249	272	317	362	408	498	544
400 × 100	13	18	24	12	53.8	296	323	377	430	484	592	646

チャンネル 一般構造用圧延鋼材 SS JIS G3101(1987)

カラー 白

サイズ			1.0	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A×B	t1	t2									
40×75	5	7	6.92	38.1	41.5	48.4	55.4	62.3	69.2	76.1	83.0
50×100	5	7.5	9.36	51.5	56.2	65.5	74.9	84.2	93.6	103	112
65×125	6	8	13.4	73.7	80.4	93.8	107	121	134	147	161
75×150	6.5	10	18.6	102	112	130	149	167	186	205	223
	9	12.5	24.0	132	144	168	192	216	240	264	288
75×180	7	10.5	21.4	118	128	150	171	193	214	235	257
80×200	7.5	11	24.6	135	148	172	197	221	246	271	295
90×200	8	13.5	30.3	167	182	212	242	273	303	333	364
90×250	9	13	34.6	190	208	242	277	311	346	381	415
	11	14.5	40.2	221	241	281	322	362	402	442	482
90×300	9	13	38.1	210	229	267	305	343	381	419	457
	10	15.5	43.8	241	263	307	350	394	438	482	526
	12	16	48.6	267	292	340	389	437	486	535	583
100×380	10.5	16	54.6	300	327	382	436	490	545	600	654
	13	20	67.3	370	404	471	538	606	673	740	808

H形鋼 建築構造用圧延材 JIS G3136(1994)

細巾系列

A×B	サイズ			質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0
	t1	t2	r									
100×50	5	7	8	9.3	55.8	65.1	74.4	83.7	93.0	102	112	121
125×60	6	8	9	13.1	78.6	91.7	105	118	131	144	157	170
150×75	5	7	8	14.0	84.0	98.0	112	126	140	154	168	182
175×90	5	8	8	18.0	108	126	144	162	180	198	216	234
200×100	5.5	8	8	20.9	125	146	167	188	209	230	251	272
248×124	5	8	8	25.1	151	176	201	226	251	276	301	326
250×125	6	9	8	29.0	174	203	232	261	290	319	348	377
298×149	5.5	8	13	32.0	192	224	256	288	320	352	384	416
300×150	6.5	9	13	36.7	220	257	294	330	367	404	440	477
346×174	6	9	13	41.2	247	288	330	371	412	453	494	536
350×175	7	11	13	49.4	296	346	395	445	494	543	593	642
396×199	7	11	13	56.1	337	393	449	505	561	617	673	729
400×200	8	13	13	65.4	392	458	523	589	654	719	785	850
446×199	8	12	13	65.1	391	456	521	586	651	716	781	846
450×200	9	14	13	74.9	449	524	599	674	749	824	899	974
496×199	9	14	13	77.9	467	545	623	701	779	857	935	1013
500×200	10	16	13	88.2	529	617	706	794	882	970	1058	1147
600×200	11	17	13	103	618	721	824	927	1030	1133	1236	1339

SN規格もあります。

広巾系列

A×B	サイズ			質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0	13.0
	t1	t2	r									
100×100	6	8	8	16.9	101	118	135	152	169	186	203	220
125×125	6.5	9	8	23.6	142	165	189	212	236	260	283	307
150×150	7	10	8	31.1	187	218	249	280	311	342	373	404
175×175	7.5	11	13	40.4	242	283	323	591	657	723	788	854
200×200	12	12	13	56.2	337	393	450	506	562	618	674	731
	8	12	13	49.9	299	349	399	449	499	549	599	649
250×250	8	13	13	65.9	395	461	527	593	659	725	791	857
	11	11	13	63.8	383	447	510	574	638	702	766	829
	9	14	13	71.8	431	503	574	646	718	790	862	933
	14	14	13	81.6	490	571	653	734	816	898	979	1061
300×300	9	14	13	86.0	516	602	688	774	860	946	1032	1118
	12	12	13	83.4	500	584	667	751	834	917	1001	1084
	10	15	13	93.0	558	651	744	837	930	1023	1116	1209
	15	15	13	105	630	735	840	945	1050	1155	1260	1365
	11	17	13	105	630	735	840	945	1050	1155	1260	1365
350×350	10	16	13	113	678	791	904	1017	1130	1243	1356	1469
	13	13	13	105	630	735	840	945	1050	1155	1260	1365
	16	16	13	129	774	903	1032	1161	1290	1419	1548	1677
	12	19	13	135	810	945	1080	1215	1350	1485	1620	1755
	19	19	13	154	924	1078	1232	1386	1540	1694	1848	2002
	14	22	13	157	942	1099	1256	1413	1570	1727	1884	2041
400×400	11	18	22	147	882	1029	1176	1323	1470	1617	1764	1911
	18	18	22	168	1008	1176	1344	1512	1680	1848	2016	2184
	16	24	22	200	1200	1400	1600	1800	2000	2200	2400	2600
	15	15	22	140	840	980	1120	1260	1400	1540	1680	1820
	18	18	22	168	1008	1176	1344	1512	1680	1848	2016	2184
	21	21	22	197	1182	1379	1576	1773	1970	2167	2364	2561
	13	21	22	172	1032	1204	1376	1548	1720	1892	2064	2236
	18	28	22	232	1392	1624	1856	2088	2320	2552	2784	3016
	20	35	22	283	1698	1981	2264	2547	2830	3113	3396	3679
	30	50	22	415	2490	2905	3320	3735	4150	4565	4980	5395
	45	70	22	605	3630	4235	4840	5445	6050	6655	7260	7865

SN規格もあります。

中巾系列

サイズ				質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A×B	t1	t2	r								
148×100	6	9	8	20.7	124	145	166	186	207	228	248
194×150	6	9	8	29.9	179	209	239	269	299	329	359
244×175	7	11	13	43.6	262	305	349	392	436	480	523
294×200	8	12	13	55.8	335	391	446	502	558	614	670
340×250	9	14	13	78.1	469	547	625	703	781	859	937
390×300	10	16	13	105	630	735	840	945	1050	1155	1260
440×300	11	18	13	121	726	847	968	1089	1210	1331	1452
488×300	11	18	13	125	750	875	1000	1125	1250	1375	1500
588×300	12	20	13	147	882	1029	1176	1323	1470	1617	1764
700×300	13	24	18	182	1092	1274	1456	1638	1820	2002	2184
800×300	14	26	18	207	1242	1449	1656	1863	2070	2277	2484
900×300	16	28	18	240	1440	1680	1920	2160	2400	2640	2880

SN規格もあります。

軽量H形鋼 一般構造用溶接軽量H形鋼 SWH400 JIS G3353(1990)

サイズ			質量kg/m	定尺(m)重量					
A × B	t1	t2		7.0	8.0	9.0	10.0	11.0	12.0
150 × 75	3.2	4.5	8.84	61.9	70.7	79.6	88.4	97.2	106
150 × 100	3.2	4.5	10.6	74.2	84.8	95.4	106	117	127
175 × 90	3.2	4.5	10.5	73.5	84.0	94.5	105	116	126
200 × 100	3.2	4.5	11.9	83.3	95.2	107	119	131	143
	3.2	6.0	14.1	98.7	113	127	141	155	169
200 × 125	3.2	6.0	16.5	116	132	148	165	182	198
200 × 150	3.2	4.5	15.4	108	123	139	154	169	185
	3.2	6.0	18.9	132	151	170	189	208	227
250 × 125	3.2	4.5	14.9	104	119	134	149	164	179
	4.5	6.0	20.2	141	162	182	202	222	242
	4.5	9.0	25.9	181	207	233	259	285	311
250 × 150	3.2	4.5	16.6	116	133	149	166	183	199
	4.5	6.0	22.5	158	180	202	225	248	270
	4.5	9.0	29.4	206	235	265	294	323	353
300 × 150	3.2	4.5	17.9	125	143	161	179	197	215
	4.5	6.0	24.3	170	194	219	243	267	292
	4.5	9.0	31.2	218	250	281	312	343	374
300 × 175	4.5	6.0	26.7	187	214	240	267	294	320
	4.5	9.0	34.7	243	278	312	347	382	416
350 × 175	4.5	6.0	28.4	199	227	256	284	312	341
	4.5	9.0	36.5	256	292	328	365	402	438
400 × 200	4.5	6.0	32.5	228	260	292	325	358	390
	4.5	9.0	41.8	293	334	376	418	460	502
	6.0	9.0	46.3	324	370	417	463	509	556
	6.0	12.0	55.4	388	443	499	554	609	665
450 × 200	4.5	9.0	43.5	304	348	392	435	478	522
	6.0	12.0	57.7	404	462	519	577	635	692



アイビーム 一般構造用圧延鋼材 SS400 JIS G3101(1987)

サイズ			1.0	5.5	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A × B	t1	t2									
75 × 75	5	8	11.9	65.4	71.4	83.3	95.2	107	119	131	143
100 × 75	5	8	12.9	71.0	77.4	90.3	103	116	129	142	155
125 × 75	5.5	9.5	16.1	88.6	96.6	113	129	145	161	177	193
150 × 75	5.5	9.5	17.1	94.0	103	120	137	154	171	188	205
150 × 125	8.5	14	36.2	199	217	253	290	326	362	398	434
180 × 100	6	10	23.6	130	142	165	189	212	236	260	283
200 × 100	7	10	26.0	143	156	182	208	234	260	286	312
200 × 150	9	16	50.4	277	302	353	403	454	504	554	605
250 × 125	7.5	11.5	38.3	211	230	268	306	345	383	421	460
	10	19	55.5	305	333	388	444	500	555	610	666
300 × 150	8	13	48.3	266	290	338	386	435	483	531	580
	10	18.5	65.5	360	393	458	524	590	655	720	786
	11.5	22	76.8	422	461	538	614	691	768	845	922
350 × 150	9	15	58.5	322	351	410	468	526	585	644	702
	12	24	87.2	480	523	610	698	785	872	959	1046
400 × 150	10	18	72.0	396	432	504	576	648	720	792	864
	12.5	25	95.8	527	575	671	766	862	958	1054	1150
450 × 175	11	20	91.7	504	550	642	734	825	917	1009	1100
	13	26	115	632	690	805	920	1035	1150	1265	1380
600 × 190	13	25	133	732	798	931	1064	1197	1330	1463	1596
	16	35	176	968	1056	1232	1408	1584	1760	1936	2112

## CT形鋼

広幅					中幅					細幅				
サイズ				質量 kg/m	サイズ				質量 kg/m	サイズ				質量 kg/m
A×B	t1	t2	r		A×B	t1	t2	r		A×B	t1	t2	r	
50×100	6	8	8	8.47	75×100	6	9	8	10.3	75×75	5	7	8	7.01
62.5×125	6.5	9	8	11.8	100×150	6	9	8	15.0	87.5×90	5	8	8	8.99
75×150	7	10	8	15.6	125×175	7	11	13	21.8	100×100	5.5	8	8	10.5
87.5×175	7.5	11	13	20.2	150×200	8	12	13	27.9	125×125	6	9	8	14.5
100×200	8	12	13	24.9	175×250	9	14	13	39.1	150×150	6.5	9	13	18.4
125×250	9	14	13	35.9	200×300	10	16	13	52.3	175×175	7	11	13	24.7
150×300	10	15	13	46.5	225×300	11	18	13	60.4	200×200	8	13	13	32.7
175×350	12	19	13	67.5	250×300	11	18	13	62.5	225×200	9	14	13	37.5
200×400	13	21	22	85.8	300×300	12	20	13	73.5	250×200	10	16	13	44.1
	18	28	22	116	350×300	13	24	18	90.9	300×200	11	17	13	51.7
	20	35	22	142	400×300	14	26	18	103					
	30	50	22	207	450×300	15	23	18	105					
	45	70	22	302		16	28	18	120					
				18		34	18	141						
				19		37	18	152						

長さにつきましてはその都度ご確認ください。

デッキプレート JIS S3352(1979)

品名	JIS呼称	厚さ	カラー		メッキ			
					Z12		Z27	
			kg/m	kg/m <sup>2</sup>	kg/m	kg/m <sup>2</sup>	kg/m	kg/m <sup>2</sup>
V50型	ALB12	1.2	8.21	13.4	8.37	13.6	8.55	13.9
	ALB16	1.6	10.9	17.8	11.0	17.9	11.2	18.2
V50A型	ALF12	1.2	8.21	13.4	8.37	13.6	8.55	13.9
	ALF16	1.6	10.9	17.8	11.0	17.9	11.2	18.2
V60型	ALG12	1.2	8.77	14.6	8.44	14.9	9.12	15.2
	ALG16	1.6	11.6	19.3	11.8	19.7	12.0	20.0
KP-1型	AKD08	0.8	5.72	8.80	5.89	9.06	6.07	9.34
	AKD12	1.2	8.46	13.0	8.63	13.3	8.81	13.6
EV50型		1.2	8.21	13.4	8.37	13.6	8.55	13.9
		1.6	10.9	17.8	11.0	17.6	11.2	18.2
EUA型		1.2	9.41	15.7	9.59	16.0	9.79	16.3
		1.6	12.5	20.8	12.6	21.0	12.8	21.3
UA型	BCL12	1.2	9.41	15.7	9.79	16.3	9.79	16.3
	BCL16	1.6	12.5	20.8	12.8	21.3	12.8	21.3
	BCL23	2.3	17.7	29.5	18.1	30.2	18.1	30.2
UA-N	ALK12	1.2	9.41	15.6	9.56	15.9	9.76	16.3
	ALK16	1.6	12.5	20.7	12.6	21.0	12.8	21.3
	ALK23	2.3	17.7	29.5	17.9	29.8	18.1	30.2
UKA型	BLD10	1.0	8.57	12.4	8.77	12.7	8.99	13.0
	BLD12	1.2	10.3	14.9	10.5	15.2	10.7	15.5
	BLD16	1.6	13.6	19.7	13.8	20.2	14.0	23.3
	BLD23	2.3	19.4	28.1	19.6	28.4	19.8	33.0
UKA-N	ALN10	1.0	8.55	12.4	8.75	12.7	8.96	13.0
	ALN12	1.2	10.2	14.8	10.4	15.1	10.6	15.4
	ALN16	1.6	13.6	19.7	13.4	20.1	14.0	20.3
	ALN23	2.3	19.3	28.0	19.5	28.3	19.7	28.6

長さに関しましてはご注文の際にお問い合わせください。

合成スラブ用デッキプレート

品名	記号	厚さ	カラー		亜鉛メッキ			
			質量	平方米当重量	Z12		Z27	
			kg/m	kg/m <sup>2</sup>	kg/m	kg/m <sup>2</sup>	kg/m	kg/m <sup>2</sup>
QLデッキ	QL99-50	1.2	7.68	12.8	7.78	13.0	7.99	13.3
		1.6	10.2	17.0	10.3	17.2	10.5	17.5
	QL300-50	1.2			4.17			
		1.6			5.52			
	QL99-75	1.2	8.36	13.9	8.46	14.1	8.69	14.5
		1.6	11.1	18.5	11.2	18.7	11.5	19.2
	QL300-75	1.2			4.49			
		1.6			5.96			
スーパーE	EZ-50	1.2	7.70	12.8	7.85	13.1	8.01	13.4
		1.6	10.2	17.0	10.3	17.2	10.5	17.5
	EZ300-50	1.6	5.14		5.21			
	EZ-75	1.2	8.36	13.9	8.52	14.2	8.70	14.5
		1.6	11.0	18.3	11.2	18.7	11.4	19.0
	EZ300-75	1.6	5.58		5.66			
MAデッキ	MA50	1.2			7.81	13.0	8.01	13.3
		1.6			10.3	17.2	10.5	17.5

各種メーカー品あります。  
長さに関しましてはご注文の際にお問い合わせください。

## レール

種類	質量 kg/m	サイズmm							断面積 cm <sup>2</sup>
	W	A	B	C	t	D	E	F	S
6	5.98	50.80	50.80	25.40	4.76	14.29	27.78	8.73	7.61
9	8.94	63.50	63.50	32.10	5.90	17.48	35.72	10.30	11.39
10	10.1	66.67	66.67	34.13	6.35	18.26	37.30	11.11	12.84
12	12.2	69.85	69.85	38.10	7.54	19.85	37.70	12.30	15.50
15	15.2	79.37	79.37	42.86	8.33	22.22	43.65	13.50	19.33
22	22.3	93.66	93.66	50.80	10.72	26.99	50.00	16.67	28.39
30	30.1	107.95	107.95	60.33	12.30	30.95	57.55	19.45	38.32
37	37.2	122.24	122.24	62.71	13.49	36.12	64.69	21.43	47.30
40	40.9	140	122	64	14	41	73.5	25.5	52
50	50.4	144.46	127	67.87	14.29	46.04	70.64	27.78	64.20
60	60.8	174	145	65	16.5	49	94.9	30.1	77.50

定尺は30フィート又は33フィートとなります。

フラットバー JIS G3101(1987)

サイズ B×A		1.0	5.5	6.0	サイズ B×A		1.0	5.5	6.0	サイズ B×A		1.0	5.5	6.0
3×	9	0.212	4m 1.17		6×	13	0.612	3.37		9×	16	1.13	6.22	
	13	0.306	1.68			16	0.754	4.15			19	1.34	7.37	
	16	0.377	2.07			19	0.895	4.92			22	1.55	8.52	
	19	0.447	2.46			22	1.04	5.72			25	1.77	9.74	10.6
	22	0.518	2.85			25	1.18	6.49	7.08		32	2.26	12.4	13.6
	25	0.589	3.24	3.53		32	1.51	8.30	9.06		38	2.68	14.7	16.1
	32	0.754	4.15	4.52		38	1.79	9.84	10.7		44	3.11	17.1	18.7
	38	0.895	4.92	5.37		44	2.07	11.4	12.4		50	3.53	19.4	21.2
	44	1.04	5.72			50	2.36	13.0	14.2		60	4.24	23.3	25.4
	50	1.18	6.49	7.08		60	2.83		17.0		65	4.59	25.2	27.5
	65	1.53	8.42			65	3.06	16.8	18.4		70	4.95		29.7
	75	1.77	9.74			70	3.30		19.8		75	5.30	29.2	31.8
	90	2.12	11.7			75	3.53	19.4	21.2		80	5.65		33.9
	100	2.36	13.0			80	3.77		22.6		90	6.36	35.0	38.2
	125	2.94	16.2			90	4.24	23.3	25.4		100	7.06	38.8	42.4
150	3.53	19.4		100	4.71	25.9	28.3	110	7.77		46.6			
4.5×	13	0.459	2.52		110	5.18		31.1	120	8.48		50.9		
	16	0.565	3.11		125	5.89	32.4	35.3	125	8.83	48.6	53.0		
	19	0.671	3.69		150	7.06	38.8	42.4	150	10.6	58.3	63.6		
	22	0.777	4.27		160	7.54		45.2	160	11.3		67.8		
	25	0.883	4.86	5.30	165	7.77		46.6	165	11.7		70.2		
	32	1.13	6.22	6.78	170	8.01		48.1	170	12.0		72.0		
	38	1.34	7.37	8.04	175	8.24		49.4	175	12.4		74.4		
	44	1.55	8.52	9.30	180	8.48		50.9	180	12.7		76.2		
	50	1.77	9.74	10.6	190	8.95		53.7	190	13.4		80.4		
	60	2.12		12.7	200	9.42		56.5	200	14.1		84.6		
	65	2.30	12.6	13.8	230	10.8		64.8	230	16.2		97.2		
	75	2.65	14.6	15.9	250	11.8		70.8	240	17.0		102		
	90	3.18	17.5	19.1	300	14.1		84.6	250	17.7		106		
	100	3.53	19.4	21.2	350	16.5		99.0	285	20.1		121		
	125	4.42	24.3						300	21.2		127		
150	5.30	29.2						350	24.7		148			
								400	28.3		170			

サイズ B×A		1.0	5.5	6.0
12×	20	1.88	10.3	
	22	2.07	11.4	
	25	2.36	13.0	14.2
	32	3.01	16.6	18.1
	38	3.58	19.7	21.5
	44	4.14	22.8	24.8
	50	4.71	25.9	28.3
	60	5.65		33.9
	65	6.12	33.7	36.7
	70	6.59		39.5
	75	7.06	38.8	42.4
	80	7.54		45.2
	90	8.48	46.6	50.9
	100	9.42	51.8	56.5
	110	10.4		62.4
	120	11.3		67.8
	125	11.8	64.9	70.8
	150	14.1	77.6	84.6
	160	15.1		90.6
	165	15.5		93.0
170	16.0		96.0	
175	16.5		99.0	
180	17.0		102	
185	17.4		104	
190	17.9		107	
200	18.8		113	
230	21.7		130	
240	22.6		136	
250	23.6		142	
285	26.8		161	
300	28.3		170	
350	33.0		198	
400	37.7		226	

サイズ B×A		1.0	5.5	6.0
14×	200	22.0		132
	25	3.14	17.3	
	32	4.02	22.1	24.1
	38	4.77	26.2	28.6
16×	44	5.53	30.4	33.2
	50	6.28	34.5	37.7
	60	7.54		45.2
	65	8.16	44.9	49.0
	70	8.79		52.7
	75	9.42	51.8	56.5
	80	10.0		60.0
	90	11.3	62.2	67.8
	100	12.6	69.3	75.6
	110	13.8		82.8
	125	15.7	86.4	94.2
	150	18.8	103	113
	160	20.1		121
	165	20.7		124
	170	21.4		128
	175	22.0		132
	180	22.6		136
	190	23.9		143
	200	25.1		151
	230	28.9		173
250	31.4		188	
300	37.7		226	
350	44.0		264	
400	50.2		301	

サイズ B×A		1.0	5.5	6.0
19×	25	3.73	20.5	
	32	4.77	26.2	28.6
	38	5.67	31.2	34.0
	44	6.56	36.1	39.4
	50	7.46	41.0	44.8
	60	8.95		53.7
	65	9.69	53.3	58.1
	70	10.4		62.4
	75	11.2	61.6	67.2
	80	11.9		71.4
	90	13.4	73.7	80.4
	100	14.9	82.0	89.4
	110	16.4		98.4
	125	18.6	102	112
	150	22.4	123	134
	175	26.1		157
	180	26.8		161
	200	29.8		179
	250	37.3		224
	300	44.7		268
350	52.2		313	
400	59.7		358	

サイズ B×A		1.0	5.5	6.0	サイズ B×A		1.0	5.5	6.0	サイズ B×A		1.0	5.5	6.0	
22×	32	5.53	30.4		25×	32	6.28	34.5		32×	50	12.6	69.3	75.6	
	38	6.56	36.1			38	7.46	41.0			65	16.3	89.6	97.8	
	44	7.60	41.8			50	9.81	54.0	58.9		75	18.8	103	113	
	50	8.64	47.5	51.8		65	12.8	70.4	76.8		90	22.6	124	136	
	65	11.2	61.6	67.2		75	14.7	80.8	88.2		100	25.1	138	151	
	70	12.1		72.6		90	17.7	97.4	106		125	31.4	173	188	
	75	13.0	71.5	78.0		100	19.6	108	118		150	37.7	207	226	
	80	13.8		82.8		125	24.5	135	147		200	50.2		301	
	90	15.5	85.2	93.0		150	29.4	162	176		250	62.8		377	
	100	17.3	95.2	104		200	39.2		235		300	75.4		452	
	110	19.0		114		250	49.1		295		350	87.9		527	
	125	21.6	119	130		300	58.9		353		400	100		600	
	150	25.9	142	155		350	68.7		412		50	14.1	77.6	84.6	
	180	31.1		187		400	78.5		471		65	18.4	101	110	
	200	34.5		207		28×	50	11.0	60.5			75	21.2	117	127
	250	43.2		259			65	14.3	78.6			100	28.3	156	170
300	51.8		311	75	16.5		90.8		125	35.3	194				
350	60.4		362	90	19.8		109		150	42.4	233				
400	69.1		415	100	22.0		121		200	56.5		339			
				125	27.5		151		250	70.6		424			
				150	33.0		182		300	84.8		509			
				200	44.0			264	350	98.9					
				250	55.0		330	400	113						
				300	65.9		395								
				350	76.9										
				400	87.9										



機械構造用炭素鋼 平鋼(標準S50C)

厚/幅	19	25	32	38	50	65	75	90	100	105	127	130	152.4	155	185	210	260	310	360	410	460	510	
6																							
9.5																							
12.7																							
13																							
16																							
19																							
22																							
23																							
25																							
27																							
28																							
32																							
38																							
45																							
50																							
55																							
65																							
75																							
85																							
95																							
105																							
115																							
125																							

機械構造用炭素鋼 平鋼 焼なまし材 (標準S55C)

厚/幅	105	130	155	185	205	255	235	275	285	305	335	355	385	405	455	505	555	605	655	705	760	810	910	1020	1300		
13																											
17																											
19																											
23																											
25																											
28																											
33																											
38																											
45																											
50																											
55																											
65																											
75																											
85																											
95																											
105																											
115																											
125																											
135																											
145																											
155																											
165																											
175																											
185																											
195																											
205																											
215																											
235																											
255																											
295																											
335																											

丸棒 JIS G3101(1987)

丸棒

サイズ	1.0	5.5	6.0
6	0.222	1.22	1.33
8	0.395	2.17	2.37
9	0.499	2.74	2.99
13	1.04	5.72	6.24
16	1.58	8.69	9.48
19	2.23	12.3	13.4
22	2.98	16.4	17.9
25	3.85	21.2	23.1
28	4.83	26.6	29.0
30	5.55	30.5	33.3
32	6.31	34.7	37.9
36	7.99	43.9	47.9
38	8.90	49.0	53.4
40	9.87	54.3	59.2
42	10.9	60.0	65.4
44	11.9	65.4	71.4
46	13.0	71.5	78.0
48	14.2	78.1	85.2
50	15.4	84.7	92.4
55	18.7	103	112
60	22.2	122	133
65	26.0	143	156
70	30.2	166	181
75	34.7	191	208
80	39.5	217	237
85	44.5	245	267
90	49.9	274	299
95	55.6	306	334
100	61.7	339	370
110	74.6	410	448
120	88.8	488	533
130	104	572	624
140	121	666	726
150	139	764	834
160	158	869	948
170	178	979	1068
180	200	1100	1200
190	223	1226	1338
200	247	1358	1482

材質はSR295、SS400、S45Cなど各種取り揃えております。

異形丸棒 JIS G3112(1987)

異形丸棒

サイズ	1.0	5.5	6.0
D10 9.53	0.56	3.08	3.36
D13 12.7	0.995	5.47	5.97
D16 15.9	1.56	8.58	9.36
D19 19.1	2.25	12.4	13.5
D22 22.2	3.04	16.7	18.2
D25 25.4	3.98	21.9	23.9
D29 28.6	5.04	27.7	30.2
D32 31.8	6.23	34.3	37.4
D35 34.9	7.51	41.3	45.1
D38 38.1	8.95	49.2	53.7
D41 41.3	10.5	57.8	63.0
D51 50.8	15.9	87.4	95.4

500ピッチの長さで3.5～8mまであります。

角鋼 JIS G3101(1987)

角鋼

サイズ	1.0	5.5
9.52	0.711	3.91
12.7	1.27	6.99
16	2.01	11.11
19	2.83	15.6
22	3.80	20.9
25	4.91	27.0
28	6.15	33.8
32	8.04	44.2
36	10.2	56.1
38	11.3	62.2
44	15.2	83.6
50	19.6	108
55	23.7	130
60	28.3	156
65	33.2	183
70	38.5	212
75	44.2	243
90	63.6	350
100	78.5	432
110	95.0	522
120	113	622
130	133	732
140	154	847
150	177	974

鋼板 JIS G3101(1987)

HOT

板厚	質量kg/m <sup>2</sup>	サイズ				
		914 × 1829	1219 × 2438	1524 × 3048	1524 × 6096	1524 × 12192
1.2	9.42	15.8	28.0			
1.6	12.56	21.0	37.3	58.3		
2.3	18.06	30.2	53.7	83.9		
3.2	25.12	42.0	74.7	117		
4	31.40	52.5	93.3	146		
4.5	35.32	59.1	105	164		
6	47.10	78.8	140	219	438	
8	62.80	105	187	292	583	
9	70.65	118	210	328	656	1313
10	78.50	131	233	365	729	1459
12	94.20	158	280	438	875	1750
14	109.9	184	327	510	1021	2042
16	125.6	210	373	583	1167	1751
19	149.2	249	443	693	1386	2772
20	157.0	263	467	729	1459	2917
22	172.7	289	513	802	1604	3209
25	196.2	328	583	911	1823	3645
28	219.8	368	653	1021	2042	4084
30	235.5	394	700	1094	2188	4376
32	251.2	420	747	1167	2334	4667
36	282.6	473	840	1313	2625	5251
40	314.0	525	933	1459	2917	5834
45	353.2	591	1050	1641	3281	6562
50	392.5	656	1167	1823	3646	7293
55	431.8	722	1283	2006	4011	8023
60	471.0	788	1400	2188	4376	8751
65	510.2	853	1516	2370	4740	9480
70	549.5	919	1633	2552	5105	10209
75	588.8	984	1750	2735	5470	
80	628.0	1050	1866	2917	5834	
100	785.0	1313	2333	3646	7293	

C形鋼 一般構造用軽量形鋼 JIS G3350(1987)

サイズ		質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A×B×C	厚さ								
60×30×10	1.6	1.63	9.78	11.4	13.0	14.7	16.3	17.9	19.6
	2.3	2.25	13.5	15.8	18.0	20.2	22.5	24.8	27.0
75×45×15	1.6	2.32	13.9	16.2	18.6	20.9	23.2	25.5	27.8
	2.3	3.25	19.5	22.8	26.0	29.2	32.5	35.8	39.0
100×50×20	1.6	2.88	17.3	20.2	23.0	25.9	28.8	31.7	34.6
	2.3	4.06	24.4	28.4	32.5	36.5	40.6	44.7	48.7
	3.2	5.50	33.0	38.5	44.0	49.5	55.0	60.5	66.0
120×60×20	2.3	4.78	28.7	33.5	38.2	43.0	47.8	52.6	57.4
	3.2	6.51	39.1	45.6	52.1	58.6	65.1	71.6	78.1
125×50×20	2.3	4.51	27.1	31.6	36.1	40.6	45.1	49.6	54.1
	3.2	6.13	36.8	42.9	49.0	55.2	61.3	67.4	73.6
150×50×20	3.2	6.76	40.6	47.3	54.1	60.8	67.6	74.4	81.1
150×65×20	3.2	7.51	45.1	52.6	60.1	67.6	75.1	82.6	90.1
150×75×20	3.2	8.01	48.1	56.1	64.1	72.1	80.1	88.1	96.1
150×75×25	3.2	8.27	49.6	57.9	66.2	74.4	82.7	91.0	99.2
200×75×20	3.2	9.27	55.6	64.9	74.2	83.4	92.7	102	111

黒・カラー・白があります。また、受注生産品もありますので、ご注文の際にお問い合わせください。

軽ミソ形鋼

サイズ		質量			
A × B	厚さ	kg/m	5.5m	6m	8m
9 × 9	1.2	0.265	1.46 (20本束売)		
40 × 20	1.6	0.939		5.63	
	2.3	1.31		7.86	
40 × 40	3.2	2.75		16.5	
60 × 30	1.6	1.44		8.64	
	2.3	2.03		12.2	
80 × 40	2.3	2.75		16.5	
100 × 40	2.3	3.11		18.7	
	3.2	4.26		25.6	
100 × 50	2.3	3.47		20.8	
	3.2	4.76		28.6	38.1
120 × 40	3.2	4.76		28.6	38.1
150 × 50	3.2	6.02		36.1	48.2
	4.5	8.31		49.9	66.5
150 × 75	4.5	10.1		60.6	80.8
	6.0	13.2		79.2	106
200 × 50	3.2	7.27		43.6	58.2
	4.0	9.00		54.0	72.0
	4.5	10.1		60.6	80.8
200 × 75	4.5	11.8		70.8	94.4
	6.0	15.6		93.6	125
250 × 50	4.0	10.6		63.6	84.8
	4.5	11.8		70.8	94.4
250 × 75	4.5	13.6		81.6	109
	6.0	17.9		107	143
300 × 50	4.0	12.1		72.6	96.8
	4.5	13.6		81.6	109
350 × 50	4.0	13.7		82.2	110
	4.5	15.4		92.4	123
400 × 75	4.5	18.9		113	151
	6.0	25.0		150	200
450 × 75	4.5	20.7		124	166
	6.0	27.3		164	218



スモール角パイプ STKMR

カラー 白

厚さ	角出し		アール付き		質量	
	A × B	A × B	A × B	A × B	kg/m	kg/5.5m
1.0	9 × 9				0.289	1.16(4m)
1.2	11 × 11				0.435	2.39
1.2	14 × 14				0.530	2.92
1.6	13 × 13				0.690	3.80
1.2	16 × 16	22 × 10			0.621	3.42
1.6	16 × 16				0.813	4.47
1.2	19 × 19	25 × 12			0.716	3.94
1.6	19 × 19	25 × 12			0.939	5.16
1.2	21 × 21				0.811	4.46
1.6	21 × 21				1.07	5.88
1.6	24 × 14				0.939	5.16
1.2	24 × 24	32 × 14	26 × 26	30 × 20	0.906	4.98
1.6	24 × 24	32 × 14	26 × 26	30 × 20	1.19	6.54
1.2	25 × 25				0.971	5.34
1.6	25 × 25				1.28	7.04
1.2		28 × 18			0.906	4.98
1.6		28 × 18			1.19	6.54
1.2	28 × 28	40 × 16	31 × 31	40 × 20	1.09	6.00
1.6	28 × 28	40 × 16	31 × 31	40 × 20	1.44	7.92
1.2	32 × 32	40 × 25			1.23	6.76
1.6	32 × 32	40 × 25			1.62	8.91
1.6		50 × 18			1.71	9.40
1.6	38 × 38	50 × 26	40 × 40	50 × 30	1.94	10.7
2.0			40 × 40		2.41	14.5(6m)
1.6	45 × 45	60 × 30			2.32	12.8
1.6		70 × 25		75 × 25	2.44	13.4
1.6		60 × 35		70 × 30	2.44	13.4
1.6				80 × 40	2.95	16.2
2.0		84 × 32		80 × 40	3.66	20.1
1.6				90 × 30	2.95	16.2
2.0				90 × 30	3.66	20.1

スーパースモール角パイプ (アール付き)

カラー 白

サイズA×B×厚さ	kg/m	6m/kg
25×25×2.3	1.67	10.0
25×25×3.2	2.26	13.6
30×30×2.3	2.03	12.2
30×30×3.2	2.75	16.5
35×35×3.2	3.30	19.8
40×40×2.3	2.62	15.7
40×40×3.2	3.58	21.5
45×45×2.3	3.10	18.6
45×45×3.2	4.25	25.5
30×20×2.3	1.67	10.0
40×20×2.3	2.03	12.2
40×20×3.2	2.75	16.5
50×30×2.3	2.62	15.7
50×30×3.2	3.58	21.5

サイズA×B×厚さ	kg/m	6m/kg
50×40×3.2	4.25	25.5
60×40×1.6	2.44	14.6
60×40×2.3	3.34	20.0
60×40×3.2	4.76	28.6
75×20×1.6	2.32	13.9
75×20×2.3	3.30	19.8
80×40×2.3	4.20	25.2
80×40×3.2	5.77	34.6
90×30×2.3	4.20	25.2
90×30×3.2	5.77	34.6
90×45×2.3	4.86	29.2
90×45×3.2	6.68	40.1
100×20×1.6	2.95	17.7
100×20×2.3	4.20	25.2

中径角形鋼管 一般構造用角形鋼管 STKR400 JIS G3466(1988)

カラー 白

サイズ		質量 kg/m	6.0	7.0	8.0	9.0	10.0
A×B	厚さ						
50×50	1.6	2.38	14.3		19.0		
	2.3	3.34	20.0		26.7		
	3.2	4.50	27.0		36.0		
	4.5	6.02	36.1				
	6.0	7.57	45.4				
60×60	1.6	2.88	17.3				
	2.3	4.06	24.4		32.5		
	3.2	5.50	33.0		44.0		
	4.5	7.43	44.6				
	6.0	9.45					
75×75	1.6	3.64	21.8				
	2.3	5.14	30.8		41.1		51.4
	3.2	7.01	42.1		56.1		
	4.5	9.55	57.3		76.4		
	6.0	12.3	73.8				
80×80	2.3	5.50	33.0				
	3.2	7.51	45.1				
90×90	2.3	6.23	37.4				
	3.2	8.51	51.1				
100×100	2.3	6.95	41.7	48.6	55.6	62.6	69.5
	3.2	9.52	57.1	66.6	76.2	85.7	95.2
	4.5	13.1	78.6	91.7	105	118	131
	6.0	17.0	102		136		170
	9.0	24.1	145		193		
	12.0	30.2					
115×115	4.5	15.0	90.0				
125×125	3.2	12.0	72.0	84.0	96.0	108	120
	4.5	16.6	99.6	116	133	149	166
	6.0	21.7	130		174		217
	9.0	31.1	187		249		
	12.0	39.7					
150×150	4.5	20.1	121	141	161	181	201
	5.0	22.3	134		178		
	6.0	26.4	158	185	211	238	264
	9.0	38.2	229	267	306	344	382
	12.0	49.1	295		393		
175×175	5.0	26.2	157		210		
	6.0	31.1	187	218	249	280	311
	9.0	45.3	272		362		453
	12.0	58.5					

カラー 白

サイズ		質量kg/m	6.0	8.0	10.0
A×B	厚さ				
50×20	1.6	1.63	9.78		
	2.3	2.25	13.5		
	3.2	3.12	18.7		
60×30	1.6	2.13	12.8		
	2.3	2.98	17.9	23.8	
	3.2	3.99	23.9	31.9	
75×45	1.6	2.88	17.3		
	2.3	4.06	24.4	32.5	
	3.2	5.50	33.0	44.0	
	4.5	7.43	44.6		
100×40	1.6	3.38	20.3		
	2.3	4.78	28.7		
	3.2	6.51	39.1		
100×50	1.6	3.64	21.8		
	2.3	5.14	30.8	41.1	51.4
	3.2	7.01	42.1	56.1	70.1
	4.5	9.55	57.3	76.4	
	6.0	12.3	73.8	98.4	
125×40	1.6	4.01	24.1		
	2.3	5.69	34.1		
	3.2	7.76			
125×75	2.3	6.95	41.7	55.6	
	3.2	9.52	57.1	76.2	95.2
	4.5	13.1	78.6	105	
	6.0	17.0	102	136	
150×50	2.3	6.95	41.7		
	3.2	9.52	57.1		
150×75	3.2	10.8	64.8	86.4	
	4.5	14.9	89.4	119	
	6.0	19.3	116	154	
150×80	4.5	15.2	91.2	122	
	6.0	19.8	119	158	
150×100	3.2	12.0	72.0	96.0	120
	4.5	16.6	99.6	133	166
	6.0	21.7	130	174	
	9.0	31.1	187	249	
200×100	4.5	20.1	121	161	201
	6.0	26.4	158	211	
	9.0	38.2	229	306	
200×150	4.5	23.7	142	190	
	6.0	31.1	187	249	
	9.0	45.3	272	362	

サイズ		質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A×B	厚さ								
250×150	6.0	35.8	215	251	286	322	358	394	430
	9.0	52.3	314	366	418	471	523	575	628
	12.0	67.9	407	475	543	611	679	747	815
300×200	6.0	45.2	271	316	362	407	452	497	542
	9.0	66.5	399	466	532	598	665	732	798
	12.0	86.8	521	608	694	781	868	955	1042
350×150	6.0	45.2	271	316	362	407	452	497	542
	9.0	66.5	399	466	532	598	665	732	798
	12.0	86.8	521	608	694	781	868	955	1042
400×200	6.0	54.7	328	383	438	492	547	602	656
	9.0	80.6	484	564	645	725	806	887	967
	12.0	106	636	742	848	954	1060	1166	1272

コラム STKR

サイズ		質量kg/m	6.0	7.0	8.0	9.0	10.0	11.0	12.0
A×B	厚さ								
200×200	4.5	27.2	163						
	6.0	35.8	215	251	286	322	358	394	430
	8.0	46.9	281	328	375	422	469	516	563
	9.0	52.3	314	366	418	471	523	575	628
	12.0	67.9	407	475	543	611	679	747	815
250×250	6.0	45.2	271	316	362	407	452	497	542
	9.0	66.5	399	466	532	598	665	732	798
	12.0	86.8	521	608	694	781	868	955	1042
	16.0	112	672	784	896	1008	1120	1232	1344
300×300	6.0	54.7	328	383	438	492	547	602	656
	9.0	80.6	484	564	645	725	806	887	967
	12.0	106	636	742	848	954	1060	1166	1272
	16.0	138	828	966	1104	1242	1380	1518	1656
	19.0	160	960	1120	1280	1440	1600	1760	1920
350×350	9.0	94.7	568	663	758	852	947	1042	1136
	12.0	124	744	868	992	1116	1240	1364	1488
	16.0	163	978	1141	1304	1467	1630	1793	1956
	19.0	190	1140	1330	1520	1710	1900	2090	2280
	22.0	217	1302	1519	1736	1953	2170	2387	2604
400×400	9.0	109	654	763	872	981	1090	1199	1308
	12.0	143	858	1001	1144	1287	1430	1573	1716
	16.0	188	1128	1316	1504	1692	1880	2068	2256
	19.0	220	1320	1540	1760	1980	2200	2420	2640
	22.0	251	1506	1757	2008	2259	2510	2761	3012
450×450	12.0	162	972	1134	1296	1458	1620	1782	1944
	16.0	213	1278	1491	1704	1917	2130	2343	2556
	19.0	250	1500	1750	2000	2250	2500	2750	3000
	22.0	286	1716	2002	2288	2574	2860	3146	3432
500×500	12.0	181	1086	1267	1448	1629	1810	1991	2172
	16.0	238	1428	1666	1904	2142	2380	2618	2856
	19.0	280	1680	1960	2240	2520	2800	3080	3360
	22.0	320	1920	2240	2560	2880	3200	3520	3840
550×550	16.0	263	1578	1841	2104	2367	2630	2893	3156
	19.0	310	1860	2170	2480	2790	3100	3410	3720
	22.0	355	2130	2485	2840	3195	3550	3905	4260

電縫管 機械構造用炭素鋼鋼管 STKM11A JIS G3445(1988)

極細径mm	t	kg/m	kg/3.66m
6.0	1.0	0.123	0.450
7.0	1.0	0.148	0.542
8.0	1.0	0.173	0.633
9.0	1.0	0.197	0.721
9.5	1.0	0.210	0.769
	1.2	0.246	0.900
10.0	1.0	0.222	0.813
	1.2	0.260	0.952
	1.6	0.331	1.21
11.0	1.0	0.247	0.904
12.0	1.0	0.271	0.992
	1.2	0.320	1.17
	1.6	0.410	1.50
12.7	1.0	0.289	1.06
	1.2	0.340	1.24
14.0	1.0	0.321	1.17
外径mm	t	kg/m	kg/5.5m
12.7	1.2	0.340	1.87
	1.6	0.438	2.41
15.9	1.2	0.435	2.39
	1.6	0.564	3.10
	2.0	0.686	3.77
17.3	1.6	0.619	3.40
19.1	1.0	0.446	2.45
	1.2	0.530	2.92
	1.6	0.690	3.80
	2.0	0.843	4.64
	2.3	0.953	5.24
22.2	1.2	0.621	3.42
	1.6	0.813	4.47
	2.0	0.996	5.48
25.4	1.2	0.716	3.94
	1.6	0.939	5.16
	2.0	1.15	6.32
	2.3	1.31	7.20
	3.2	1.75	9.62
27.2	1.6	1.01	5.56
28.6	1.2	0.811	4.46
	1.6	1.07	5.88
	2.0	1.31	7.20

外径mm	t	kg/m	kg/5.5m
31.8	1.2	0.906	4.98
	1.6	1.19	6.54
	2.0	1.47	8.08
	2.3	1.67	9.18
34.0	1.2	0.971	5.34
	1.6	1.28	7.04
	2.0	1.58	8.69
	2.3	1.80	9.90
35.0	1.2	1.00	5.50
38.1	1.2	1.09	6.00
	1.6	1.44	7.92
	2.0	1.78	9.79
	2.3	2.03	11.2
42.7	1.2	1.23	6.76
	1.6	1.62	8.91
	2.3	2.29	12.6
45.0	1.6	1.71	10.3(6m)
	2.0	2.12	12.1(5.7m)
48.6	1.6	1.85	10.2
	2.3	2.63	14.5
50.8	1.2	1.47	8.08
	1.6	1.94	10.7
	2.0	2.41	13.3
	2.3	2.75	16.5(6m)
54.0	1.6	2.07	11.4
60.5	1.6	2.32	12.8
	2.0	2.89	15.9
63.5	1.6	2.44	13.4
70.0	1.6	2.70	14.8
76.3	1.6	2.95	16.2
	2.0	3.66	20.1
80.0	1.6	3.09	17.0
89.1	1.6	3.45	20.7(6m)
101.6	1.6	3.95	23.7(6m)
ミガキSGP		kg/m	kg/5.5m
P15A		1.31	7.20
P20A		1.68	9.24
P25A		2.43	13.4
P32A		3.38	18.6
P40A		3.89	21.4

印はメッキ品の在庫もあります。

ガス管 配管用炭素鋼鋼管 SGP JIS G3452(1988)

白 ネジ付有り

呼称 記号A	インチ名 記号B	外径	厚さ	質量 kg/m	1本当り kg/5.5m
6A	1/8B	10.5	2.0	0.419	2.30
8A	1/4B	13.8	2.3	0.652	3.59
10A	3/8B	17.3	2.3	0.851	4.68
15A	1/2B	21.7	2.8	1.31	7.20
20A	3/4B	27.2	2.8	1.68	9.24
25A	1B	34.0	3.2	2.43	13.4
32A	1 1/4B	42.7	3.5	3.38	18.6
40A	1 1/2B	48.6	3.5	3.89	21.4
50A	2B	60.5	3.8	5.31	29.2
65A	2 1/2B	76.3	4.2	7.47	41.1
80A	3B	89.1	4.2	8.79	48.3
90A	3 1/2B	101.6	4.2	10.1	55.6
100A	4B	114.3	4.5	12.2	67.1
125A	5B	139.8	4.5	15.0	82.5
150A	6B	165.2	5.0	19.8	109
175A	7B	190.7	5.3	24.2	133
200A	8B	216.3	5.8	30.1	166
225A	9B	241.8	6.2	36.0	198
250A	10B	267.4	6.6	42.4	233
300A	12B	318.5	6.9	53.0	292
350A	14B	355.6	7.9	67.7	372
400A	16B	406.4	7.9	77.6	427
450A	18B	457.2	7.9	87.5	481
500A	20B	508.0	7.9	97.4	536



構造用鋼管 一般構造用炭素鋼鋼管 STK400 JIS G3444(1988)

白

外径	厚さ	質量kg/m	5.5m	6m	12m
21.7	1.9	0.928	5.10	5.57	
	2.3	1.10	6.05		
27.2	1.9	1.19	6.54	7.14	
	2.3	1.41	7.76	8.46	
34.0	2.3	1.80	9.90	10.8	
	3.2	2.43	13.4	14.6	
42.7	2.3	2.29	12.6	13.7	
	3.2	3.12	17.2	18.7	
	3.5	3.38	18.6	20.3	
48.6	2.3	2.63	14.5	15.8	
	3.2	3.58	19.7	21.5	
	3.5	3.89	21.4	23.3	
60.5	2.3	3.30	18.2	19.8	
	2.8	3.98	21.9	23.9	
	3.2	4.52	24.9	27.1	54.2
	3.8	5.31		31.9	63.7
76.3	2.8	5.08	27.9	30.5	61.0
	3.2	5.77	31.7	34.6	69.2
	4.2	7.47		44.8	89.6
89.1	2.8	5.96	32.8	35.8	71.5
	3.2	6.78		40.7	81.4
	3.5	7.39		44.3	88.7
	4.2	8.79		52.7	105
	5.5	11.3		67.8	136
101.6	3.2	7.76	42.7	46.6	93.1
	4.2	10.1		60.6	121
	5.7	13.5		81.0	162
114.3	3.5	9.56	52.6	57.4	115
	4.0	10.9		65.4	131
	4.5	12.2		73.2	146
	6.0	16.0		96.0	192
127.0	4.5	13.6	74.8	81.6	
139.8	3.5	11.8	64.9	70.8	142
	4.0	13.4		80.4	161
	4.5	15.0		90.0	180
	6.6	21.7		130	260
152.4	5.0	18.2		109	
165.2	3.7	14.7		88.2	176
	4.5	17.8		107	214
	5.0	19.8		119	238
	7.1	27.7		166	332

外径	厚さ	質量kg/m	6m	12m
190.7	5.3	24.2	145	290
216.3	4.5	23.5	141	282
	5.8	30.1	181	361
	8.2	42.1	253	505
	12.7	63.8	383	766
241.8	6.2	36.0	216	432
267.4	5.8	37.4	224	449
	6.6	42.4	254	509
	9.3	59.2	355	710
	12.7	79.8	479	958
318.5	6.0	46.2	277	554
	6.9	53.0	318	636
	7.9	60.5	363	726
	10.3	78.3	470	940
	12.7	95.8	575	1150
355.6	6.4	55.1	331	661
	7.9	67.7	406	812
	9.5	81.1	487	973
	11.1	94.3	566	1132
	12.7	107	642	1284
	16.0	134	804	1608
406.4	6.4	63.1	379	757
	7.9	77.6	466	931
	9.5	93.0	558	1116
	12.7	123	738	1476
	16.0	154	924	1848
	19.0	182	1092	2184
457.2	6.4	71.1	427	853
	7.9	87.5	525	1050
	9.5	105	630	1260
	12.7	139	834	1668
	16.0	174	1044	2088
	19.0	205	1230	2460
	22.0	236	1416	2832
508.0	6.4	79.2	475	950
	7.9	97.4	584	1169
	9.5	117	702	1404
	12.7	155	930	1860
	16.0	194	1164	2328
	19.0	229	1374	2748
	22.0	264	1584	3168

外径	厚さ	質量kg/m	6m	12m
558.8	6.4	87.2	523	1046
	7.9	107	642	1284
	9.5	129	774	1548
	12.7	171	1026	2052
	16.0	214	1284	2568
	19.0	253	1518	3036
	22.0	291	1746	3492
609.6	6.4	95.2	571	1142
	7.9	117	702	1404
	9.5	141	846	1692
	12.7	187	1122	2244
	16.0	234	1404	2808
	19.0	277	1662	3324
	22.0	319	1914	3828
660.4	6.4	103	618	1236
	7.9	127	762	1524
	9.5	152	912	1824
	12.7	203	1218	2436
711.2	6.4	111	666	1332
	7.9	137	822	1644
	9.5	164	984	1968
	12.7	219	1314	2628
	16.0	274	1644	3288
762	7.9	147	882	1764
	9.5	176	1056	2112
	12.7	235	1410	2820
812.8	7.9	157	942	1884
	9.5	188	1128	2256
	12.7	251	1506	3012
	16.0	314	1884	3768
914.4	7.9	177	1062	2124
	9.5	212	1272	2544
	12.7	282	1692	3384
	16.0	354	2124	4248
1016	9.5	236	1416	2832
	12.7	314	1884	3768
	16.0	395	2370	4740
1066	9.5	248	1488	2976
	12.7	330	1980	3960
1219	9.5	283	1698	3396
	12.7	378	2268	4536

配管用アーク溶接炭素鋼管 STPY400 JIS G3457

呼称	外径	厚さ	質量 kg/m	1本当り重量	
				6m	12m
350A	355.6	6.0	51.7	310	
		6.4	55.1	331	
		7.9	67.7	406	
		12.7	107	642	
400A	406.4	6.0	59.2	355	
		6.4	63.1	379	757
		7.9	77.6	466	931
		9.5	93.0	558	
		12.7	123	738	
450A	457.2	6.0	66.8	401	
		6.4	71.1	427	853
		7.9	87.5	525	1050
		9.5	105	630	
500A	508.0	6.0	74.3	446	
		6.4	79.2	475	950
		7.9	97.4	584	1169
		9.5	117	702	
550A	558.8	6.0	82.2	496	
		6.4	87.2	523	1046
		7.9	107	642	1284
		9.5	129	774	1548
600A	609.6	6.0	89.3	536	
		6.4	95.2	571	1142
		7.9	117	702	1404
		9.5	141	846	1692
		12.7	187	1122	2244

呼称	外径	厚さ	質量 kg/m	1本当り重量	
				6m	12m
650A	660.4	6.4	103	618	1236
		7.9	127	762	1524
		9.5	152	912	1824
700A	711.2	6.0	104	624	
		6.4	111	666	1332
		7.9	137	822	1644
		9.5	164	984	1968
		12.7	219	1314	2628
750A	762.0	7.9	147	882	1764
		9.5	176	1056	2112
		12.7	235	1410	2820
800A	812.8	7.1	141	846	
		8.0	159	954	1908
		9.5	188	1128	2256
900A	914.4	12.7	251	1506	3012
		8.0	179	1074	2148
		9.5	212	1272	2544
1000A	1016.0	12.7	282	1692	3384
		9.0	223	1338	2676
		9.5	236	1416	2832
		10.3	255	1530	3060
1100A	1066.0	12.7	314	1884	3768
		10.0	273	1638	3276
1200A	1219.2	9.5	283	1698	3396
		11.1	331	1986	3972
		12.7	378	2268	4536

圧力配管用鋼管 JIS G3454(STPG)

定尺5.5m

呼び径 (A)	外径	呼び厚さ											
		スケジュール10		スケジュール20		スケジュール30		スケジュール40		スケジュール60		スケジュール80	
		厚さ	重量kg/m	厚さ	重量kg/m	厚さ	重量kg/m	厚さ	重量kg/m	厚さ	重量kg/m	厚さ	重量kg/m
6	10.5							1.7	0.369	2.2	0.450	2.4	0.479
8	13.8							2.2	0.629	2.4	0.675	3.0	0.799
10	17.3							2.3	0.851	2.8	1.00	3.2	1.11
15	21.7							2.8	1.31	3.2	1.46	3.7	1.64
20	27.2							2.9	1.74	3.4	2.00	3.9	2.24
25	34.0							3.4	2.57	3.9	2.89	4.5	3.27
32	42.7							3.6	3.47	4.5	4.24	4.9	4.57
40	48.6							3.7	4.10	4.5	4.89	5.1	5.47
50	60.5			3.2	4.52			3.9	5.44	4.9	6.72	5.5	7.46
65	76.3			4.5	7.97			5.2	9.12	6.0	10.4	7.0	12.0
80	89.1			4.5	9.39			5.5	11.3	6.6	13.4	7.6	15.3
90	101.6			4.5	10.8			5.7	13.5	7.0	16.3	8.1	18.7
100	114.3			4.9	13.2			6.0	16.0	7.1	18.8	8.6	22.4
125	139.8			5.1	16.9			6.6	21.7	8.1	26.3	9.5	30.5
150	165.2			5.5	21.7			7.1	27.7	9.3	35.8	11.0	41.8
200	216.3			6.4	33.1	7.0	36.1	8.2	42.1	10.3	52.3	12.7	63.8
250	267.4			6.4	41.2	7.8	49.9	9.3	59.2	12.7	79.8	15.1	93.9
300	318.5			6.4	49.3	8.4	64.2	10.3	78.3	14.3	107	17.4	129
350	355.6	6.4	55.1	7.9	67.7	9.5	81.1	11.1	94.3	15.1	127	19.0	158
400	406.4	6.4	63.1	7.9	77.6	9.5	93.0	12.7	123	16.7	160	21.4	203
450	457.2	6.4	71.1	7.9	87.5	11.1	122	14.3	156	19.0	205	23.8	254
500	508.0	6.4	79.2	9.5	117	12.7	155	15.1	184	20.6	248	26.2	311

引抜鋼管 (STKM)

定尺6m

外径	厚さ														
	2.6	3.2	3.5	4.0	4.5	5.0	6.0	9.0	10	12	14	15	18	20	25
15	0.795	0.931	0.993	1.09	1.17	1.23									
20	1.12	1.33	1.42	1.58	1.72	1.85	2.07								
25	1.44	1.72	1.86	2.07	2.27	2.47	2.81								
27.2	1.58	1.89	2.05	2.29	2.52	2.74	3.14								
30	1.76	2.11	2.29	2.56	2.83	3.08	3.55	4.66							
31.8	1.87	2.26	2.44	2.74	3.03	3.30	3.82	5.06	5.38						
38.1	2.28	2.75	2.99	3.36	3.73	4.08	4.75	6.46	6.93						
40	2.40	2.90	3.15	3.55	3.94	4.32	5.03	6.88	7.40						
42.7	2.57	3.12	3.38	3.82	4.24	4.65	5.43	7.48	8.06	9.08					
48.6	2.95	3.58	3.89	4.40	4.89	5.38	6.30	8.79	9.52	10.8	11.9				
50.8	3.09	3.76	4.08	4.62	5.14	5.65	6.63	9.28	10.1	11.5	12.7				
60.5	3.71	4.52	4.92	5.57	6.21	6.84	8.06	11.4	12.5	14.4	16.1				
65	4.00	4.88	5.31	6.02	6.71	7.40	8.73	12.4	13.6	15.7	17.6	18.5			
70	4.32	5.27	5.74	6.51	7.27	8.01	9.47	13.5	14.8	17.2	19.3	20.3	23.1		
76.3	4.73	5.77	6.28	7.13	7.97	8.79	10.4	14.9	16.3	19.0	21.5	22.7	25.9		
82.6		6.27	6.83	7.75	8.67	9.57	11.3	16.3	17.9	20.9	23.7	25.0	28.7	30.9	
89.1		6.78	7.39	8.39	9.39	10.4	12.3	17.8	19.5	22.8	25.9	27.4	31.6	34.1	
101.6			8.47	9.63	10.8	11.9	14.1	20.6	22.6	26.5	30.2	32.0	37.1	40.2	47.2
114.3				10.9	12.2	13.5	16.0	23.4	25.7	30.3	34.6	36.7	42.7	46.5	55.1
130					13.9	15.4	18.3	26.9	29.6	34.9	40.0	42.5	49.7	54.3	64.7
139.8					15.0	16.6	19.8	29.0	32.0	37.8	43.4	46.2	54.1	59.1	70.7
152.4					16.4	18.2	21.7	31.8	35.1	41.5	47.1	50.8	59.7	65.3	
165.2					17.8	19.8	23.6	34.7	38.3	45.3	52.2	55.6	65.3	71.6	86.4
168.3					18.2	20.1	24.0	35.4	39.0	46.3	53.3	56.7	66.7	73.1	88.3
177.8						21.3	25.4	37.5	41.4	49.1	56.6	60.2	71.0	77.8	94.2
190.7						22.9	27.3	40.3	44.6	52.9	61.0	65.0	76.7	84.3	102
200						24.0	28.7	42.4	46.9	55.6	64.2	68.4	80.8	88.8	108
216.3							31.1	46.0	50.9	60.5	69.8	74.5	88.0	96.8	118
219.1							31.5	46.6	51.6	61.3	70.8	75.5	89.3	98.2	120
241.8							34.9	51.7	57.2	68.0	78.6	83.9	99.3	109	134
244.5							35.3	52.3	57.8	68.8	79.6	84.9	101	111	135
267.4							38.7	57.3	63.5	75.6	87.5	93.4	111	122	149
273.1							39.5	58.6	64.9	77.3	89.5	95.5	113	125	153
298.5								64.3	71.1	84.8	98.2	105	125	137	169
318.5								68.7	76.1	90.7	105	112	133	147	181
355.6								76.0	85.2	102	118	126	150	166	204
381								82.3	91.2	109	126	135	161	178	219

## 楕円パイプ

### オーバル管

A	B	母管
15	8	12.7
18	12.5	15.9
22	15	19.1
22.5	14	19.1
28	16	22.2
31	16	25.4
34	14	25.4
35	19	28.6
40	10	28.6
40	20	31.8
50	20	38.1
50	20	45
50	30	42.7
71	22	50.8
72	22	50.8
76	40	60.5
84	28	60.5
95	50	76.3
100	45	76.3
120	60	89.1

### 偏平楕円

A	B	母管
15	8	12.7
18	12	15.9
20	8	15.9
23	12	19.1
24	10	19.1
25	9.5	19.1
25.5	15.5	22.2
28	12	22.2
29	10	22.2
30	16	25.4
31	15	25.4
32.5	12	25.4
34	19	28.6
35	16	28.6
37	14	28.6
38.5	20	31.8
40	16	31.8
42	20	34
44	16	34
45	25	38.1
46	24	38.1
48	20	38.1
50	30	42.7
54	28	45
59	20	45
58	30	48.6
64.5	20	48.6
68	20	50.8
76.5	32	60.5
80	25	60.5
100	35	76.3